

## PETRONAS WELLBORE WS 601

is a highly effective all-in-one solution that provides optimal cleaning results and allows cleaning tasks to be done in a time  $\vartheta$  cost-efficient manner.

PCG recommends concentration of 15% for optimum cleaning performance

Product Properties

PETRONAS WELLBORE WS 601	TYPICAL VALUES*	UNITS	TESTING METHOD
Appearance	Dark brown liquid	-	In-house method
Initial Boiling Point	200	°C	ASTM D86
Flash Point	103	°C	ASTM D93 (PMCC)
Specific Gravity @ 20°C	0.89 — 1.00	-	In-house method
Kinematic Viscosity @ 40°C	1.20	mm2/s	ASTM D445
pH (1 wt% in water)	5.0-7.0	-	In-house method

<sup>\*</sup>These properties are typical but do not constitute specifications.

Key Benefits

## **PRODUCT**

PETRONAS WELLBORE WS 601

## **KEY BENEFITS**

- Solvent-surfactant system creating a stable emulsion system
- Excellent wellbore cleanliness—Faster achievement of TSS & Turbidity level
- Compatible with freshwater and seawater
- $\bullet$  Water rinsing readiness for water-wet finishing at casing & pipe surfaces
- Single-stage solution—Lower storage at rigsite

**Product Applications** 





Wellbore Cleaning